

Technical University of Denmark



WAsP prediction errors due to site orography

Mortensen, Niels Gylling

Publication date:
2005

[Link back to DTU Orbit](#)

Citation (APA):
Mortensen, N. G. (2005). WAsP prediction errors due to site orography. Abstract from WAsP days '05, Risø, Denmark.

DTU Library
Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


WAsP prediction errors due to site orography

Niels G. Mortensen
Wind Energy Department
Risø National Laboratory

WAsP Days '05
24-25 January 2005

Outline

- Accumulation of orographic prediction errors
- WAsP basics in complex terrain
 - Size of map
 - Contour line interval
 - Spot height elevations
- Wind speed correlations
- Site ruggedness
 - Speed-up ratio
 - Relative relief
 - Std. dev. of elevations
 - Flow separation
 - Site ruggedness index RIX
 - Orographic performance indicator ΔRIX



Background



- European Wind Atlas, Vol. II: *Measurements and Modelling in Complex Terrain*. Multi-partner EU project from 1990-95.
- Bowen, A.J. and N.G. Mortensen (2004). WAsP prediction errors due to site orography. Risø-R-995(EN). Risø National Laboratory, Roskilde. 65 pp.
- Bowen, A.J. and N.G. Mortensen (1996). Exploring the limits of WAsP: the Wind Atlas Analysis and Application Program. Proc. *1996 European Union Wind Energy Conference*, Göteborg, 584-587.
- Rathmann, O., N.G. Mortensen, L. Landberg and A. Bowen (1996). Assessing the accuracy of WAsP in non-simple terrain. Proc. *8th British Wind Energy Association Conference*, Exeter, 413-418.
- Mortensen, N.G. and E.L. Petersen (1998). Influence of topographical input data on the accuracy of wind flow modelling in complex terrain. Proc. *1997 European Wind Energy Conference*, Dublin, 317-320.

Accumulation of orographic prediction errors

- Application procedure

$$U_A + (\Delta U_2 + E_2) = U_{Pe}$$

- Analysis procedure

$$U_M - (\Delta U_1 + E_1) = U_A$$


- Combined procedure, eliminating U_A

$$(U_M - \Delta U_1 + \Delta U_2) + (E_2 - E_1) = U_{Pe}$$


- The correct estimation is then made up of

$$U_{Pm} = U_M - \Delta U_1 + \Delta U_2 \quad (\text{perfect prediction})$$


$$U_{Pe} = U_{Pm} + (E_2 - E_1) \quad (\text{prediction error!})$$




Case study in northern Portugal



Modelling errors and map size I





The similarity principle – revisited


The predictor and the predicted site should be as similar as possible

- Topographical setting
 - Ruggedness index (RIX)
 - Elevation and exposure
 - Distance to significant roughness changes (coastline)
 - Background roughness lengths
- Climatic conditions
 - Same regional wind climate (synoptic and meso-scale)
 - General forcing effects
 - Atmospheric stability


This means that the basic input data should also be similar

- WAsP map
 - Map size
 - Contour interval
 - Accuracy and detail
 - Roughness classification
 - ...


Cross-correlation of wind speeds




Prediction error vs. speed-up ratio




Prediction error vs. relative relief difference



Prediction error vs. RMS height difference




Prediction error vs. RIX difference




The Ruggedness Index – revisited

- Reanalyses of the Portuguese data set
 - Larger, more detailed and accurate maps
 - Improved RIX calculation (WAsP or ME)
 - More calculation radii: 72 rather than 12
 - RIX configuration corresponds to BZ-model
- Data analysis and presentation
 - Asymmetry in plot of speed error vs. ΔRIX
 - speed error was defined as $(U_p/U_m - 1)$
 - not obvious which trend line(s) to fit...
 - Substitute $\log(U_p/U_m)$ for $(U_p/U_m - 1)$
 - Easier to fit a trend line...?


Maps for RIX calculation and test




- Hand-digitised map
 - 8 by 8 km²
 - 50- 10-m contours
- SRTM-derived map
 - 20 km radius
 - 50-, 10- and 5-m contours



Wind speed error vs. Δ RIX (new maps etc.)



$\log(U_p/U_m)$ vs. ΔRIX



Things to test...


- Wind speed prediction error is (almost) fixed...
 - Number of sectors
 - Modelling parameters
- RIX configuration can be varied easily
 - Original configuration somewhat arbitrary
 - Different calculation radii (3, 3.5, 4, and 5 km)
 - Calculation radius that provides max. RIX?
 - Different critical slopes (0.30, 0.35, 0.40, 0.45)
 - Matrix of R^2 for different set-up's
- Weighting RIX with wind rose frequencies

Influence of RIX radius and critical slope


Radius R [m]	Critical slope θ_c			
	0.30	0.35	0.40	0.45
3000	0.960	0.967	0.978	0.973
3500	0.972	0.974	0.984	0.986
4000	0.971	0.978	0.982	0.979
5000	0.969	0.977	0.979	0.973

R^2 for different values of the calculation radius and critical slope.

Recalculation – best fit values



Recalculation – weighted with wind rose



Conclusions

- The similarity principle
 - WAsP inputs (maps) should also be similar, of course
- Performance indicator ΔRIX
 - Concept reinforced using new and better data
- Relation between wind speed error and ΔRIX
 - Linear relation between $\log(U_p/U_m)$ and ΔRIX
 - Relation not very sensitive to calculation radius R
 - Relation not very sensitive to the critical slope θ_c
 - ΔRIX weighted with the wind rose does not improve the relation between $\log(U_p/U_m)$ and ΔRIX